

Bona Craft Oil

Technical data sheet

Finishing



Bona Craft Oil is a unique blend of different vegetable oils, modified for superior impregnation and long-lasting protection of wooden floors. The exclusive blend is low in odour, easy to handle and gives a reduced yellowing effect. The formulation is environmentally responsible, containing much oil and little solvents (<4%) which also means that the wood can be saturated with fewer applications. Suitable for wooden floors in public and domestic environments as well as for furniture and other woodwork.

- Extremely high degree of saturation
- Rapid drying and easy to apply
- Low solvent content and low odour
- Safe for application on children's toys and countertops, EN 71-3 compliant

Technical data

Product base:	Modified vegetable oils
Colours:	Pure, Graphite, Frost, Ash, Umbra and Clay
Solids content:	Approx. 96-98% (depending on colour)
VOC:	<4%
Dilution:	Do not dilute
Drying time:	- Between applications: 15-30 minutes* - Light use: 24 hours* <i>*under normal indoor conditions, 20 °C/60% R.H. Ensure proper ventilation.</i>
Application tools:	Oil resistant rubber applicator, Bona WoolPad or stainless steel trowel
Total consumption:	Approx. 20 m ² /litre depending on wood type
Safety:	Unclassified
Fire risk:	Non flammable. Risk of self ignition, see safety data sheet for more information.
Cleaning:	Clean tools with white spirit. Dried material can be removed with white spirit.
Shelf life:	2 years, from the date of production, in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Sizes:	2,5 & 5 litre

Bona[®]