

MATERIAL SAFETY DATA SHEET

1/4

1. Identification of the preparation and company.		Date of issue: 15-01-2008
Product name and/or code: Junckers SYLVA CLEANER		Replaces: 20-02-2007
Company name, full address and telephone number: Junckers Industrier A/S Vaerftsvej 4 DK-4600 Koege Denmark Telephone: Int + 45 56 65 18 95 Email: teknik@junckers.dk		Emergency phone number: Junckers Industrier A/S Vaerftsvej 4 DK-4600 Køge Phone: Int + 45 56 65 18 95
Product type: Cleaner.	Additional component: -	Intended use: Cleaning of wood floors

2. Hazards identification.

In accordance with EC Directive 1999/45/EC the product is labelled as: **Xi Irritant.**

Contains: Propan-2-ol.

Risk-phrases: Irritating to eyes.

3. Composition/Information on ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substance Directive 67/548/EEC.

Name	EINECS-no.	Conc. (%)	Symbol	R-phrases (*)
Non-ionic tenside	-	5-15	Xi	38-41
Alcohols, C13-ethoxylated 8EO (CAS-nr. 69011-36-5)	500-241-6	< 5	Xn	22-41
Propan-2-ol	200-661-7	< 5	Xi,F	11-36-67

(*) for full text see Section 16.

4. First aid measures.

General:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation:	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.
Eye contact:	Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
Skin contact:	Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion:	If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

MATERIAL SAFETY DATA SHEET

2/4

5. Fire fighting measures.

Extinguishing media:

Recommended: Alcohol resistant foam, CO₂, powder, water spray.

Not to be used: Water jet.

Recommendations:

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Appropriate breathing apparatus may be required.

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

6. Accidental release measures.

Refer to protective measures listed in sections 7 and 8. Contain and collect spillage and place in container for disposal according to local regulations (see section 13).

Clean preferably with water; avoid use of solvents.

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

7. Handling and storage.

Handling:

Keep container tightly closed.

Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this preparation. Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8.

Never use pressure to empty : container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws.

Storage:

Observe the label precautions. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

MATERIAL SAFETY DATA SHEET

3/4

8. Exposure controls/Personal protection.

Engineering Measures:

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Exposure Limits.

Occupational exposure limit for:

Substance	ppm	mg/m ³	Substance	ppm	mg/m ³
* Propan-2-ol	200	490			

Those marked '**' are assigned by the supplier of the substance.

'Sk' indicates a risk of absorption through the skin. 'Sen' indicates a respiratory sensitiser.

Personal protection:

Respiratory protection:

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

Hand protection:

Use rubber latex gloves. Barrier (=wearing) time: 1 hour. Dispose immediately after use. See manufacturers recommendations. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection:

Use safety eyewear designed to protect against splash of liquids.

Skin protection:

Personnel should wear anti-static clothing made of natural fibre.

9. Physical and chemical properties.

Physical state:	Liquid	Colour:	Clear
pH concentrated:	8,5	pH, Diluted for use:	7
Specific gravity, kg/l:	0,99		

10. Stability and reactivity.

Stable under recommended storage and handling conditions (see section 7). When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke etc.. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

11. Toxicological information.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly.

Exposure to concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis.

The liquid splashed in the eyes may cause irritation and reversible damage.

MATERIAL SAFETY DATA SHEET

4/4

12. Ecological information.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

13. Disposal considerations.

Wastes, including emptied containers, should be disposed of in accordance with waste regulations. Waste code: 20 01 29 Detergents containing dangerous ingredients.

14. Transport information.

The product is not classified as dangerous for carriage.

ADR/RID:

-

IMDG:

-

IATA:

-

15. Regulatory information.

Limitations for use: Not to be used by persons under 18 years of age.

In accordance with EC Directive 1999/45/EC the product is labelled as follows:

Symbol:

Xi



Irritant

Contains: Propan-2-ol.

Risk-phrases: Irritating to eyes.

Safety-phrases: Keep out of reach of children.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

If swallowed, seek medical advice immediately and show this container or label.

Others:

-

16. Other information.

Full text of R-phrases appearing in section 2:

R11: Highly flammable.
R22: Harmful if swallowed.
R36: Irritating to eyes.
R38: Irritating to skin.
R41: Risk of serious damage to eyes.
R67: Vapours may cause drowsiness and dizziness.

The information in this Safety Data Sheet is required pursuant to the EC Directive 91/155/EC.

The information of this SDS is based on the present state of our knowledge and on current EU and national laws. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product : it is not to be considered as a guarantee of the products' properties.